# **Future Module**

| FM-203                     |  |                |
|----------------------------|--|----------------|
| Model No.                  | FM-203   |                |
| Power Consumption          | 140W   |                |
| Temperature Range          | 200-450°C  |                |
| Temperature Stability      | ±5°C at idle temperature                           |                |
| Station                    |  |                |
| Output                     | 24V  |                |
| Dimensions                 | 120(W) × 120(H) × 190(D)mm                         |                |
| Weight                     | 2.7kg  |                |
| FM-2027                    |  |                |
| Model No.                  | FM-2027  |                |
| Power Consumption          | 70W (24V)  |                |
| Tip to Ground Resistance   | < 2Ω   |                |
| Tip to Ground Potential    | < 2s2  |                |
| Total Length (w/o cord)    | 188mm with 2.4D tip                                |                |
| Weight (w/o cord)          | 30g with 2.4D tip                                  |                |
| Cord                       | 1.2m   |                |
| MODEL FM-2022/MO           | DEL EM-2022  |                |
| Model No.                  | FM-2022  | FM-2023        |
| Power Consumption          | -  |                |
| Temperature Range          | 140W (24V)<br>200-400°C                            |                |
| Tip to Ground Resistance   | < 2Ω   |                |
| Tip to Ground Potential    | < 232<br>< 2mV                                     |                |
| Total Length (w/o cord)    | 148mm with SOP 25L tip                             |                |
| Weight (w/o cord)          | 64g with SOP 25L tip                               | 37g with I tip |
| Cord                       |  | 2m             |
| MODEL FM-2024              |  |                |
| Model No.                  | FM-2024  |                |
| Power Consumption          | FM-2024<br>70W (24V)                               |                |
| Temperature Range          | 350-450°C  |                |
| Tip to Ground Potential    | < 2mV  |                |
| Tip to Ground Resistance   | < 2Ω   |                |
| Total Length (w/o cord)    | 180mm with ø1.0 nozzle                             |                |
| Weight (w/o cord & hose)   | 65g with ø1.0 nozzle                               |                |
| Cord                       | 1.2m   |                |
| Desolder Control Box       | x  |                |
| Power Consumption          | 12W  |                |
| Output                     | 24V  |                |
| Vacuum Generator           | Ejector type                                       |                |
| Vacuum Pressure (Max.)     | 93kPa (700mmHg)                                    |                |
| Suction Flow               | 28ℓ/min.   |                |
| Nozzle to Ground Potential | < 2mV  |                |
| Applied Air Pressure       | 490kPa (5.0kgf/cm <sup>2</sup> ) when in use       |                |
| Compressed Air Consumption | (trigger or button is pressed)                     |                |
| Dimensions                 | 1.62 c.f.m (46ℓ/min.)<br>119(W) x 45(H) x 172(D)mm |                |
|                            | 1.2kg  |                |

#### Replacement Tips and Nozzles

FM-2027: Please refer to pages 16-17. MODEL FM-2022, MODEL FM-2023, MODEL FM-2024: Please refer to page 13.

## N<sub>2</sub> System



Combination sample with the N2 system HAKKO FM-203, HAKKO FM-2026, HAKKO FX-780, HAKKO FX-791 For further details, refer to pages 18-21.

| Packing List                      |                                   |  |
|-----------------------------------|-----------------------------------|--|
| <u> </u>                          |                                   |  |
| Model Name                        | Contents                          |  |
| HAKKO FM-203                      | Station                           |  |
|                                   | Soldering iron (FM-2027) ·····    |  |
|                                   | Power cord                        |  |
|                                   | Iron holder with 599B tip cleaner |  |
|                                   | (No.FH200-01)                     |  |
|                                   | Control card                      |  |
|                                   | Connecting cable                  |  |
|                                   | Tip tray                          |  |
|                                   | Heat resistant pad                |  |
|                                   | * Tip is an optional part.        |  |
| HAKKO FM-2027<br>(Conversion kit) | Soldering iron (FM-2027) ·····    |  |
|                                   | Iron holder with 599B tip cleaner |  |
|                                   | (No.FH200-01)                     |  |
|                                   | Connecting cable                  |  |
|                                   | Heat resistant pad                |  |
|                                   |                                   |  |

#### cleaner \* Tip is an optional part. Parallel remover (MODEL FM-2022) ··· ...1 Iron holder with cleaning sponge HAKKO (No.FH200-03) ·· MODEL FM-2022 Connecting cable -(Conversion kit) Heat resistant pad-\* Tip is an optional part. Mini parallel remover (MODEL FM-2023) .....1 Tips (T9-I/2pcs of set) ... Iron holder with cleaning sponge HAKKO MODEL FM-2023 (No.FH200-04) --(Conversion kit) Connecting cable Heat resistant pad .. Component bed ····· Desoldering tool (MODEL FM-2024) ····· ....1 Desolder control box (DCB) ···· Iron holder with 599B tip cleaner (No.FH200-05).. HAKKO MODEL FM-2024 Connecting cable -Cleaning drill . (Conversion kit) Ceramic paper filter---·10 Filter pipe assembly. Handle (for gun configuration) --Nozzle remover-


### **Replacement Parts**


| Name/Description                                  |
|---|
| Soldering iron FM-2027/Connector assembly 24V-70W |
| Parallel remover MODEL FM-2022/24V-140W           |
| Mini parallel remover MODEL FM-2023/24V-140W      |
| Desoldering tool MODEL FM-2024/24V-70W            |
| Sleeve assembly/yellow                            |
| Sleeve assembly/blue                              |
| Sleeve assembly/orange                            |
| Sleeve assembly/ green                            |
| Tip cleaner                                       |
| Connecting cable                                  |
| Ceramic paper filter/10 pcs                       |
| Front holder                                      |
| Filter pipe assembly                              |
| Tip tray  |
|   |


\* Nozzle is an optional part.

Replacement Tips and Nozzles

T16 Series For MODEL FM-2022







Unit : mm

13