# **Material Safety Data Sheet**





Revision Number: 003.0

## **1. PRODUCT AND COMPANY IDENTIFICATION**

Product name: Product type: **422 Super Bonder® Instant Adhesive** Cyanoacrylate

**Company address:** Henkel Corporation One Henkel Way Rocky Hill, Connecticut 06067 IDH number:233927Item number:42250Region:United StatesContact information:Telephone:860.571.5100MEDICAL EMERGENCY Phone:Poison Control Center1-877-671-4608 (toll free) or 1-303-592-1711TRANSPORT EMERGENCY Phone:CHEMTREC1-800-424-9300 (toll free) or 1-703-527-3887Internet:www.henkelna.com

# 2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW				
Physical state: Color: Odor:	Liquid Clear, Colorless Sharp, Irritating	HMIS: HEALTH: FLAMMABILITY: PHYSICAL HAZARD: Personal Protection:	2 2 1 See MSDS Section 8	
WARNING:	COMBUSTIBLE LIQ BONDS SKIN IN SE MAY CAUSE EYE, S	UID AND VAPOR.		
Relevant routes of exposure: Skin, Inhalation, Eyes				
Potential Health Effects				
Inhalation:		above the established exposure limit res		
Skin contact:	Bonds skin in secon allergic reaction but Cyanoacrylates gen	ds. May cause skin irritation. Cyanoaci due to rapid polymerization at the skin s erate heat on solidification. In rare circui	rylates have been reported to cause surface, an allergic response is rare. mstances a large drop will burn the	
Eye contact: Ingestion:	Irritating to eyes. Ca Not expected to be	skin. Cured adhesive does not present a health hazard even if bonded to the skin. Irritating to eyes. Causes excessive tearing. Eyelids may bond. Not expected to be harmful by ingestion. Rapidly polymerizes (solidifies) and bonds in mouth. It is almost impossible to swallow.		
Existing conditions aggrave exposure:	vated by Eye, skin, and respi	ratory disorders.		
	This material is cons 1910.1200).	sidered hazardous by the OSHA Hazard	Communication Standard (29 CFR	

See Section 11 for additional toxicological information.

# 3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous components	CAS NUMBER	%
Ethyl 2-cyanoacrylate	7085-85-0	60 - 100
Thickener	Proprietary	10 - 30

	4. FIRST AID MEASURES
Inhalation:	Move to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. If symptoms develop and persist, get medical attent
Skin contact:	Do not pull bonded skin apart. Soak in warm soapy water. Gently peel ap using a blunt instrument. If skin is burned due to the rapid generation of I by a large drop, seek medical attention. If lips are bonded, apply warm wa to the lips and encourage wetting and pressure from saliva in mouth. Pee roll lips apart. Do not pull lips apart with direct opposing force.
Eye contact:	Immediately flush with plenty of water for at least 15 minutes. Get medica attention. If eyelids are bonded closed, release eyelashes with warm wat covering with a wet pad. Do not force eye open. Cyanoacrylate will bond eye protein and will cause a lachrymatory effect which will help to debonc adhesive. Keep eye covered until debonding is complete, usually within 1 days. Medical attention should be sought in case solid particles of polyme cyanoacrylate trapped behind the eyelid caused abrasive damage.
Ingestion:	Ensure breathing passages are not obstructed. The product will polymeriz rapidly and bond to the mouth making it almost impossible to swallow. Sa will separate any solidified product in several hours. Prevent the patient fr swallowing any separated mass.
Notes to physician:	Surgery is not necessary to separate accidentally bonded tissues. Experi- has shown that bonded tissues are best treated by passive, non-surgical aid. If rapid curing has caused thermal burns they should be treated symptomatically after adhesive is removed.
	5. FIRE FIGHTING MEASURES

Flash point:	80 - 93.4 °C (176°F - 200.12 °F) Tagliabue closed cup
Autoignition temperature:	485 °C (905°F)
Flammable/Explosive limits - lower:	Not determined
Flammable/Explosive limits - upper:	Not determined
Extinguishing media:	Water spray (fog), foam, dry chemical or carbon dioxide.
Special firefighting procedures:	Fire fighters should wear positive pressure self-contained breathing apparatus (SCBA).
Unusual fire or explosion hazards:	None
Hazardous combustion products:	Trace amounts of toxic and/or irritating fumes may be released and the use of breathing apparatus is recommended.

# 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions:	Ventilate area.
Clean-up methods:	Do not use cloths for mopping up. Flood with water to complete polymerization and scrape off the floor. Cured material can be disposed of as non-hazardous waste.

### 7. HANDLING AND STORAGE

Handling:

Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling. Avoid contact with fabric or paper goods. Contact with these materials may cause rapid polymerization which can generate smoke and strong irritating vapors, and cause thermal burns.

Storage:

Keep in a cool, well ventilated area away from heat, sparks and open flame. Keep container tightly closed until ready for use.

For information on product shelf life contact Henkel Customer Service at (800) 243-4874.

### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous components	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Ethyl 2-cyanoacrylate	0.2 ppm TWA	None	None	None
Thickener	None	None	None	None
Engineering controls:	Use positive down-draft exhaust ventilation if general ventilation is insufficient to maintain vapor concentration below established exposure limits.			
Respiratory protection:	Use a NIOSH approved air-purifying respirator with an organic vapor cartridge.			
Eye/face protection:	Safety goggles or safety glasses with side shields.			
Skin protection:	Use nitrile gloves and aprons as necessary to prevent contact. Do not use PVC, nylon or cotton.			

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Color: Odor: Odor threshold: pH: Vapor pressure: Boiling point/range: Melting point/ range: Specific gravity: Vapor density: Flash point: Flammable/Explosive limits - lower: Flammable/Explosive limits - upper: Autoignition temperature: Evaporation rate: Solubility in water: Partition coefficient (n-octanol/water): VOC content:

Liquid Clear, Colorless Sharp, Irritating 1 - 2 ppm Not applicable < 0.5 mm hg (25 °C (77°F)) > 100 °C (> 212°F) Not determined 1.1 at 20 °C (68°F) 3 Approximately 80 - 93.4 °C (176°F - 200.12 °F) Tagliabue closed cup Not determined Not determined 485 °C (905°F) Not available. Polymerises in presence of water. Not determined < 2 %; < 20 g/l (California SCAQMD Method 316B) (Estimated)

	10. STAB	ILITY AND	REACTIVITY	
Stability:		Stable under re	commended storage conditions.	
Hazardous reactions:		Rapid exothermic polymerization will occur in the presence of water, amines, alkalis and alcohols.		
Hazardous decomposition products	:	None		
Incompatible materials:		Water, amines,	alkalis and alcohols.	
Conditions to avoid:		Spontaneous po	olymerization.	
1'	1. TOXICO	LOGICAL I	NFORMATION	
Acute oral product toxicity:		LD50 (rat) > 5,0	000 mg/kg (Estimated)	
Acute dermal product toxicity:		LD50 (rabbit) >	2,000 mg/kg (Estimated)	
lazardous components	NTP Car	cinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Ethyl 2-cyanoacrylate	N	-	No	No
hickener	N	0	No	No
lazardous components			Health Effects/Target	Organs
thyl 2-cyanoacrylate			Irritant, Allergen, Resp	piratory
hickener			Irritant	
	formation pro	vided is for un	IDERATIONS used product only. state, federal and provincial reg	julations for disposal.
Hazardous waste number:		Not a RCRA hazardous waste.		
	14. TRAN	ISPORT INI	FORMATION	
U.S. Department of Transportation C Proper shipping name: Hazard class or division: Identification number: Packing group: International Air Transportation (ICA Proper shipping name: Hazard class or division: Identification number: Packing group: Exceptions:	Comi Comi NA 1 III O/IATA) Aviat 9 UN 3 III Prima	bustible liquid, n bustible Liquid 993 ion regulated liq 334 ary packs contai	.o.s. (Cyanoacrylate ester) uid, n.o.s. (Cyanoacrylate ester ning less than 500ml are unreg	, ,
Water Transportation (IMO/IMDG) Proper shipping name: Hazard class or division: Identification number: Packing group:		egulated	FFFF and other	

#### **15. REGULATORY INFORMATION**

**United States Regulatory Information** 

TSCA 8 (b) Inventory Status:	All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.	
TSCA 12(b) Export Notification:	None above reporting de minimus	
CERCLA/SARA Section 302 EHS: CERCLA/SARA Section 311/312: CERCLA/SARA 313:	None above reporting de minimis Immediate Health, Delayed Health, Fire, Reactive None above reporting de minimis	
California Proposition 65:	No California Proposition 65 listed chemicals are known to be present.	
Canada Regulatory Information		
CEPA DSL/NDSL Status:	Contains one or more components listed on the Non-Domestic Substances List. All other components are listed on or are exempt from listing on the Domestic Substances List. Components listed on the NDSL must be tracked by all Canadian Importers of Record as required by Environment Canada. They may be imported into Canada in limited quantities. Please contact Regulatory Affairs for additional details.	
WHMIS hazard class:	B.3, D.2.B	
16. OTHER INFORMATION		

#### This material safety data sheet contains changes from the previous version in sections: 1

Prepared by: Kyra Kozak Woods, Manager, Regulatory Affairs

**DISCLAIMER:** The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.