

Revision Number: 003.0

1. PRODUCT AND COMPANY IDENTIFICATION

Product name: Product type:

Loctite(R) Encap(R) 3141 Epoxy Resin Epoxy resin

Company address: Henkel Corporation One Henkel Way Rocky Hill, Connecticut 06067 IDH number: 233530 Item number: 39947 Region: United States Contact information: Telephone: 860.571.5100 MEDICAL EMERGENCY Phone: Poison Control Center 1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT ENERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887 Internet: www.henkelna.com

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW				
HMIS:				
Physical state:	Liquid	HEALTH: *2		
Color:	Black	FLAMMABILITY: 1		
Odor:	Aromatic	PHYSICAL HAZARD: 0		
		Personal Protection: See MSDS Section 8		
WARNING	: MA	Y CAUSE ALLERGIC SKIN REACTION.		
	MA	Y CAUSE EYE, SKIN AND RESPIRATORY TRACT IRRITATION.		
Relevant routes of exposure: Skin, Inhalation, Eyes				
Potential Health Effect	<u>s</u>			
Inhalation:		May cause respiratory tract irritation.		
Skin contact:		May cause allergic skin reaction. May cause skin irritation.		
Eye contact:		May cause irritation.		
Ingestion:		Not expected under normal conditions of use.		
U				
Existing conditions aggravated by exposure:		Eye, skin, and respiratory disorders. Skin allergies.		
		This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).		

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous components	CAS NUMBER	%
Epichlorohydrin-4,4'-isopropylidene diphenol resin	25068-38-6	30 - 60
Quartz (SiO2)	14808-60-7	30 - 60
Calcium carbonate	471-34-1	10 - 30
Neopentyl glycol diglycidyl ether	17557-23-2	0.1 - 1
Carbon black	1333-86-4	0.1 - 1

4. FIRST AID MEASURES

Inhalation:

Move to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. If symptoms develop and persist, get medical attention.

Skin contact:	Immediately flush skin with plenty of water (using soap, if available). Remove contaminated clothing and footwear. If symptoms develop and persist, get medical attention. Wash clothing before reuse. Thoroughly clean shoes before reuse.
Eye contact:	Immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention.
Ingestion:	DO NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention.
	5. FIRE FIGHTING MEASURES
Flash point:	249 °C (480.2 °F) Closed cup
Autoignition temperature:	Not available.

Autoignition temperature:	NOL AVAIIADIE.
Flammable/Explosive limits - lower:	Not available.
Flammable/Explosive limits - upper:	Not available.
Extinguishing media:	Water spray (fog), foam, dry chemical or carbon dioxide.
Special firefighting procedures:	Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.
Unusual fire or explosion hazards:	Closed containers may rupture (due to build up of pressure) when exposed to extreme heat. In case of fire, keep containers cool with water spray.
Hazardous combustion products:	Oxides of carbon. Irritating vapors.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions:	Do not allow product to enter sewer or waterways.
Clean-up methods:	Ensure adequate ventilation. Wear appropriate personal protective equipment. Refer to Section 8 "Exposure Controls / Personal Protection" prior to clean up. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Scrape up spilled material and place in a closed container for disposal.

7. HANDLING AND STORAGE		
Handling:	Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling. Use only with adequate ventilation. Keep container closed.	
Storage:	Keep container tightly closed and in a cool, well-ventilated place away from incompatible materials. Keep away from heat, spark and flame. Protect from direct sunlight.	

For information on product shelf life contact Henkel Customer Service at (800) 243-4874.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous components	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Epichlorohydrin-4,4'-isopropylidene diphenol resin	None	None	None	None
Quartz (SiO2)	0.025 mg/m3 TWA Respirable fraction.	2.4 MPPCF TWA Respirable. 0.1 mg/m3 TWA Respirable. 0.3 mg/m3 TWA Total dust.	None	None
Calcium carbonate	10 mg/m3 TWA Total dust.	5 mg/m3 TWA Respirable fraction. 15 mg/m3 TWA Total dust.	None	None
Neopentyl glycol diglycidyl ether	None	None	None	None
Carbon black	3 mg/m3 TWA Inhalable fraction.	3.5 mg/m3 TWA	None	None

Engineering controls:

Use local ventilation if general ventilation is insufficient to maintain vapor concentration below established exposure limits.

Use NIOSH approved respirator if there is potential to exceed exposure

Respiratory protection:

Skin protection:

Eye/face protection:

Safety goggles or safety glasses with side shields.

Use chemical resistant, impermeable clothing including gloves and either an apron or body suit to prevent skin contact. Suitable glove materials may include: EVAL-Laminate gloves. Nitrile gloves. Butyl rubber gloves. PVC gloves.

9. PHYSICAL AND CHEMICAL PROPERTIES

limit(s).

Physical state:
Color:
Odor:
Odor threshold:
pH:
Vapor pressure:
Boiling point/range:
Melting point/ range:
Specific gravity:
Vapor density:
Flash point:
Flammable/Explosive limits - lower:
Flammable/Explosive limits - upper:
Autoignition temperature:
Evaporation rate:
Solubility in water:
Partition coefficient (n-octanol/water):
VOC content:

Liquid Black Aromatic Not available. Not available. Not available. > 149 °C (> 300.2 °F) Not available. 1.6 Not available. 249 °C (480.2 °F) Closed cup Not available. Not available. Not available. Not available. Insoluble Not available. < 1 %; < 10 g/l

10. STABILITY AND REACTIVITY

Stability:	Stable under normal conditions of storage and use.
Hazardous reactions:	None under normal processing.
Hazardous decomposition products:	Oxides of carbon. Irritating vapors.
Incompatible materials:	Oxidizing agents. Acids. Bases. Amines.
Conditions to avoid:	Keep away from heat, ignition sources and incompatible materials. Protect from direct sunlight.

11. TOXICOLOGICAL INFORM	ATION
--------------------------	-------

Hazardous components	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Epichlorohydrin-4,4'-isopropylidene diphenol resin	No	No	No
Quartz (SiO2)	Known To Be Human Carcinogen.	Group 1	No
Calcium carbonate	No	No	No
Neopentyl glycol diglycidyl ether	No	No	No
Carbon black	No	Group 2B	No

Hazardous components	Health Effects/Target Organs		
Epichlorohydrin-4,4'-isopropylidene diphenol resin	Allergen, Irritant		
Quartz (SiO2)	Immune system, Lung, Some evidence of carcinogenicity		
Calcium carbonate	Nuisance dust		
Neopentyl glycol diglycidyl ether	Allergen, Blood, Bone Marrow, Immune system, Irritant, Reproductive		
Carbon black	Respiratory, Some evidence of carcinogenicity		

12. ECOLOGICAL INFORMATION

Ecological information:

Hazardous waste number:

Not available.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal:

Not a RCRA hazardous waste.

14. TRANSPORT INFORMATION

The shipping classifications in this sections are for non-bulk packaging only (unless otherwise specified). Shipping classification may be different for bulk packaging.

U.S. Department of Transportation Ground (4	<u>19 CFR)</u>
Proper shipping name:	Not regulated
Hazard class or division:	None
Identification number:	None
Packing group:	None
International Air Transportation (ICAO/IATA)	
Proper shipping name:	Environmentally hazardous substance, liquid, n.o.s. (Bisphenol-A Epichlorhydrin resin)
Hazard class or division:	9
Identification number:	UN 3082
Packing group:	III
Water Transportation (IMO/IMDG)	
Proper shipping name:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Bisphenol-A Epichlorhydrin resin)
Hazard class or division:	9
Identification number:	UN 3082
Packing group:	III
Marine pollutant:	Bisphenol-A Epichlorhydrin resin
15. REGULATORY INFORMATION	

United States Regulatory Information

TSCA 8 (b) Inventory Status:

All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.

Follow all local, state, federal and provincial regulations for disposal.

TSCA 12(b) Export Notification:	None above reporting de minimus	
CERCLA/SARA Section 302 EHS: CERCLA/SARA Section 311/312: CERCLA/SARA 313:	None above reporting de minimis Immediate Health, Delayed Health None above reporting de minimis	
California Proposition 65:	This product contains a chemical known in the State of California to cause cancer. This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.	
Canada Regulatory Information		
CEPA DSL/NDSL Status:	All components are listed on or are exempt from listing on the Canadian Domestic Substances List.	
WHMIS hazard class:	D.2.A, D.2.B	
16. OTHER INFORMATION		

This material safety data sheet contains changes from the previous version in sections: 1, 5, 6, 7, 8, 10

Prepared by: Rena Petrides, Regulatory Affairs Specialist

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.