



4700-SS STATICIDE® DIAMOND ESD PAINT

This cost-effective, carbon-loaded, water-based polyurethane coating dissipates static discharge for cost-effective static control. Designed for interior concrete floors and unfinished surfaces, this ESD paint is perfectly suited for EPA manufacturing areas, static-controlled workspaces, data centers, warehouses, and creating Faraday cages.

Use ACL 10R Primer as a sealer for concrete before applying the 4700-SS Diamond ESD Paint. This non-toxic primer dries clear and is ready-to-use. It provides enduring protection against water penetration damage on unsealed concrete. Made in the USA.

- ✳ Dark gray with satin sheen
- ✳ Static dissipative: 10^5 – 10^8 ohms when tested according to ANSI/ESD STM7.1
- ✳ Appropriate for facilities following ANSI/ESD S20.20

Product #4700-SS1: Gallon pail

Product #4700-SS5: 5-gallon pail

Product #ACL 10R-1: Sealer/Primer: Gallon pail

Product #ACL 10R-5: Sealer/Primer: 5-gallon pail

Product #8095: Grounding Strips: 2" x 12" (1.4 mil thickness)



#4700-SS

6700 ESD VINYL PAINT PLUS

This water-based acrylic vinyl coating is available in dissipative or conductive resistances. Suitable for interior concrete floors, walls, metal and wood surfaces. Color options allow for demarcating ESD work areas and for specific applications. Made in the USA.

- ✳ Various colors available with flat matte finish
- ✳ Static dissipative: 10^5 – 10^8 ohms when tested according to ANSI/ESD STM7.1
- ✳ Static conductive: 10^3 – 10^6 ohms when tested according to ANSI/ESD STM7.1
- ✳ Appropriate for facilities following ANSI/ESD S20.20

Product #6700: Gallon pail

Product #6700: 5-gallon pail

See website for colors and part numbers



#6700

NEUTRAL CLEANERS

These anti-static cleaners are low-foaming and produce constant detergency. They can be used in all facilities, as they leave no film or streaks, and are safe for septic and sewage systems. Anti-static properties of the production environment will not be degraded with these non-abrasive cleaners. Made in the USA.

- ✳ For use on concrete, ESD tile, and painted floors
- ✳ Ideal for maintaining ESD paint
- ✳ Available in concentrate and ready-to-use

Neutral Cleaner Concentrate - Dilution ratio: 1:128 (1 part cleaner to 128 parts water)

Product #4020-1: Gallon bottle / 4 gallons per case

Product #4020-5: 5-gallon pail

Product #4020-2: 54-gallon drum

Neutral Cleaner Ready-to Use

Product #4030-1: Gallon bottle / 4 gallons per case

Product #4030-5: 5-gallon pail

Product #4030-2: 54-gallon drum



#4020

(800) 782-8420



(847) 981-9212



www.aclstaticide.com