

Type	ATZ3710A	ATZ3711A
Number of inputs	1	1
Input voltage	0~360V DC	0~360V DC
Input current	0~30A DC	0~30A DC
Input power	0~150W	0~300W
Voltage accuracy	0.000~3.999V:0.2%+3mV	0.000~3.999V:0.2%+3mV
	4.00~35.99V:0.2%+3mV	4.00~35.99V:0.2%+3mV
	36.0~360.0V:0.2%+30mV	36.0~360.0V:0.2%+30mV
Current accuracy	0.000~2.999A:0.2%+3mA	0.000~2.999A:0.2%+3mA
	3.00~30.00A:0.2%+30mV	3.00~30.00A:0.2%+30mV
Minimum resolution	Voltage 1mV, Current 1mA	Voltage 1mV, Current 1mA
Lowest conductive resistance	<0.08Ω	<0.08Ω
Ripple	<10mVpp	<10mVpp
Interface	RS232/RS485/USB*	
Protection	Over voltage/over current/over power/over temperature	
Program Memory	10 steps program, EEPROM	
AC Input	110/220 AC +/-15%, 47~63Hz	
Operating environment	0~50 °C, 80% RH	
Software	Electronic load software, ActiveX and DLL tool for VB VC++	
Weight	5.0kg	
Dimensions	212.6 x 88.1 x 250	
Standard accessories	User's manual, Accable handle bars	