



LED Distribution Box terminaLED®

## terminaLED® P 3050 - triple distribution box for LED spots in parallel connections



### Technical data

<b>Connection</b>	IDC (insulation displacement connector) 3 x 2 clamping units 0.34 – 0.5 mm <sup>2</sup> (IN, LED, OUT)
<b>Fixing</b>	centrally by screw M3,5 or with a glued rear side
<b>Mouldings</b>	polyamide 6/6, dark grey flammability rating to UL 94: V-2 continuous working temperature 100 °C short-time temperature 160 °C
<b>Cables</b>	XYFAZ 2 x 0.5 mm <sup>2</sup> , flexible twin cable red/black on reels, 50 metres or 100 metres to be ordered separately as accessories
<b>Contacts</b>	bronze, plated
<b>Voltage rating</b>	150 V according EN 60 598-1
<b>Current rating</b>	6 A (0.5 mm <sup>2</sup> ) resp. 5 A (0.34 mm <sup>2</sup> ) at T 60 °C
<b>Protection class</b>	IP20

## Order info

<b>Description</b>	<b>Item</b>	<b>Order No.</b>	<b>PU</b>
LED distribution box	terminalLED® P 3050	605103	50
Cables 50 meters	XYFAZ 2 x 0,5 50	609950	1
Cable 100 metres	XYFAZ 2 x 0,5 100	6099X0	1