

TAPERED HEAD

LENGTH 4.5" (115 MM)

MODEL	L	A	B	C	MAX. Cu	WEIGHT	DESCRIPTION
595T	4.5" (115 mm)	0.47" (12 mm)	0.41" (10.5 mm)	0.26" (6.5 mm)	* ask for cutting cap.	2.36 oz. (67 g)	Semi-flush cut, Tungsten Carbide blades, anti-glare finish, ESD safe Side cutter with Tungsten Carbide blades for constant quality cuts. Resistant to small stainless steel wires. Ask for special application.
595E	4.5" (115 mm)	0.35" (9 mm)	0.41" (10.5 mm)	0.26" (6.5 mm)	∅ 0.05" (1.2 mm)	2.36 oz. (67 g)	Flush cut, high grade tool steel, anti-glare finish, ESD safe, resharpenable Side cutter for universal use. Medium size.
E595E (Not Shown)	4.5" (115 mm)	0.35" (9 mm)	0.41" (10.5 mm)	0.26" (6.5 mm)	∅ 0.05" (1.2 mm)	2.36 oz. (67 g)	Flush cut, high grade tool steel, anti-glare finish, ESD safe, resharpenable Side cutter for universal use. Medium size. Same as 595E but with Ergonomic Grips.

* Please provide wire sample.

LENGTH 5.5" (140 MM)

MODEL	L	A	B	C	MAX. Cu	WEIGHT	DESCRIPTION
2222EA	5.5" (140 mm)	0.39" (10 mm)	0.39" (10 mm)	0.23" (5.8 mm)	∅ 0.04" (1.0 mm)	2.47 oz. (70 g)	Flush cut, high grade tool steel, anti-glare finish, ESD safe, resharpenable, ergonomic Ergonomic side cutter for universal use. Tapered head for easier access.

RELIEVED HEAD



RELIEVED HEAD

Main application: cutting applications in confined areas.



LENGTH 4.33" (110 MM)

MODEL	L	A	B	C	MAX. Cu	WEIGHT	DESCRIPTION
622NB	4.33" (110 mm)	0.35" (9 mm)	0.35" (9 mm)	0.24" (6 mm)	∅ 0.03" (0.8 mm)	1.69 oz. (48 g)	Flush cut, high grade tool steel, anti-glare finish, ESD safe, resharpenable Miniature side cutter. Super fine relieved head allows very good access. Economical line.
E622NB	4.33" (110 mm)	0.35" (9 mm)	0.35" (9 mm)	0.24" (6 mm)	∅ 0.03" (0.8 mm)	1.69 oz. (48 g)	Flush cut, high grade tool steel, anti-glare finish, ESD safe, resharpenable Miniature side cutter. Super fine relieved head allows very good access. Economical line. Same as 662NB but with ergonomic grips.