

Specification Of TLS 2200®/TLS PC Link™ Thermal Transfer Portable Printer Labels

Application(s): Asset Tracking, Barcoding, Component ID, Equipment ID, General Identification, General Purpose ID, Patch Panel - ID Port, Rating Plates, Through Hole - Top

Agency Approval(s)/Compliance: AGA Approved, CSA Approved, Halogen-Free (DIN VDE 0472/parts 815), UL Recognized

Size: 0.750" W x 0.250" H (19.050 mm W x 6.350 mm H)

Printable Area: 0.750" W x 0.250" H (19.050 mm W x 6.350 mm H)

Max Characters Per Line For Font #2: 18

Max Lines of Text For Font #2: 2

Label Type/Style: Label

Color: White

Finish: Gloss

Qty Per Row: 1

Material Type: Polyester

Material Description: Permanent Polyester

Brady Material #: B-423

Safety Catalog: pg. 270

General ID Catalog: pg. 39

Recommended Ribbon Series: R6010

Suggested Ribbon Part#: R6010

Acceptable Ribbon Series: R6210, R4410 (colors)

After Process: Yes, this material will work with this application

Printer Compatibility: BMP71, TLS 2200, TLS-PC Link

Surface: Smooth

Through Hole Technology: No, this material does not work with this application

RoHS Compatibility: Pass 2002/95/EC

QTY/UOM: 750/Roll