

Specification Of Thermal Transfer Printable Labels

Application(s): Communications Cables, Voice/Data Identification

Agency UL Recognized

Approval(s)/Compliance:

Size: 1.500" W x 1.500" H (38.100 mm W x 38.100 mm H)

Printable Area: 1.500" W x 0.500" H (38.100 mm W x 12.700 mm H)

Web Width: 1.700" (43.18 mm)

Label Type/Style: Self-Laminating Label

Vertical Repeat: 1.625" (41.28 mm)

Color: White/Translucent

Finish: Matte

Qty Per Row: 1

Material Type: Vinyl

Material Description: Self-Laminating Vinyl

Brady Material #: B-427

General ID Catalog: pg. 155

Recommended Ribbon Series: 4300

Suggested Ribbon Part#: R4306

Acceptable Ribbon Series: 6200, 4500 (colors)

Printer Compatibility: BBP81, Brady 1244, Brady 1344, Brady 200MVP Plus, Brady 2461, Brady 300MVP Plus, Brady 300X-Plus II, Brady 3481, Brady 360X-Plus II, Brady 600X-Plus II, Brady 6441, Tagus T200, Tagus T300, Thermal Transfer Printers

Style: Roll-Form, Radius Corners

Special Properties: Excellent abrasion and smudge resistance, Excellent water & oil resistance, Self-Extinguishing, Self-Laminating

RoHS Compatibility: Pass 2002/95/EC

QTY/UOM: 2,500/Roll