

Specification Of Thermal Transfer Printable Labels

Application(s): Circuit Board ID, Component ID, SMT - Top/Bottom, Through Hole - Bottom, Through Hole - Top

Size: 0.650" W x 0.200" H (16.510 mm W x 5.080 mm H)

Printable Area: 0.650" W x 0.200" H (16.510 mm W x 5.080 mm H)

Web Width: 2.950" (74.93 mm)

Label Type/Style: Label

Vertical Repeat: 0.300" (7.62 mm)

Horizontal Repeat: 0.700" (17.78 mm)

Color: Amber

Finish: Matte

Qty Per Row: 4

Material Type: Polyimide

Material Description: High Temperature Polyimide

Brady Material #: B-426

General ID Catalog: pg. 140

**Recommended
Ribbon Series:** 4300

**Suggested Ribbon
Part#:** R4300

After Process: Yes, this material will work with this application

Printer Compatibility: BBP81, Brady 1244, Brady 1344, Brady 200MVP Plus, Brady 2461, Brady 300MVP Plus, Brady 300X-Plus II, Brady 3481, Brady 360X-Plus II, Brady 600X-Plus II, Brady 6441, IP300, IP600, Tagus T200, Tagus T300, Thermal Transfer Printers

**Surface Mount
Technology:** Yes, this material will work with this application

**Through Hole
Technology:** Top: Yes, Bottom: Yes

Special Properties: Withstands extremely high temperatures

RoHS Compatibility: Pass 2002/95/EC

QTY/UOM: 10,000/Roll