



TIPS

**ST SERIES TIPS FOR WP25 / WP30 / WP35 IRONS
TINNED WITH LEAD FREE SOLDER**




SCREWDRIVER

Cat No.	A		C	
	IN.	MM	IN.	MM
ST1	0.062	1.58	0.75	19.05
ST2	0.093	2.38	0.75	19.05
ST3	0.125	3.17	0.75	19.05
ST4	0.187	4.74	0.75	19.05
ST6	0.031	0.79	0.75	19.05
ST8	0.062	1.58	0.75	19.05



SINGLE FLAT

Cat No.	A		C	
	IN.	MM	IN.	MM
ST5	0.031	0.79	0.75	19.05




CONICAL

Cat No.	A		C	
	IN.	MM	IN.	MM
ST7	0.031	0.79	0.75	19.05




TIPS

**CT SERIES TIPS FOR W60P AND W100P IRONS
TINNED WITH LEAD FREE SOLDER**



CT5 SERIES SCREWDRIVER

600° F Cat. No.	700° F Cat. No.	800° F Cat. No.	900° F Cat. No.
-	CT5A7	CT5A8	-
-	-	CT5B8	-
-	CT5C7	CT5C8	-
-	CT5D7	CT5D8	-
-	CT5E7	CT5E8	-
CT6C6	CT6C7	CT6C8	-
CT6D6	CT6D7	CT6D8	-
CT6E6	CT6E7	CT6E8	-
CT6F6	CT6F7	CT6F8	CT6F9
-	CT6G7	-	-



CT6 SERIES SCREWDRIVER

FITS IRON	A		C	
	IN.	MM	IN.	MM
W60P	0.062	1.58	1.15	29.36
W60P	0.093	2.38	1.15	29.36
W60P	0.125	3.17	1.15	29.36
W60P	0.187	4.74	1.15	29.36
W60P	0.250	6.35	1.15	29.36
W100P	0.125	3.17	1.37	34.92
W100P	0.187	4.74	1.37	34.92
W100P	0.250	6.35	1.37	34.92
W100P	0.375	9.52	1.37	34.92
W100P	-	-	1.37	34.92



1-800-381-7308 514-388-7308

www.diverseelectronics.com

sales@diverseelectronics.com



PROFESSIONAL

SOLDERING IRONS / 25 WATT / 30 WATT / 35 WATT

- Ideal for a wide variety of electronic tasks
- Uses ST series long life double-coated iron-plated tips- ST3 included-see page 43
- Quick change knurled collar, stainless steel barrel
- Cushion grip handle and plug-in heating element
- 6' 3-wire cord, iron is 7 7/8" long
- UL and cUL listed (120 VAC units only)



WP25

Catalog Number

WP25
WP30
WP35

Description

25 watts, 120 V, 750° F Professional soldering iron, 3-wire cord
30 watts, 120 V, 800° F Professional soldering iron, 3-wire cord
35 watts, 120 V, 850° F Professional soldering iron, 3-wire cord

CONTROLLED OUTPUT

SOLDERING IRONS / 60 WATT / 100 WATT

- Uses Weller "closed loop" method of controlling maximum tip temperature
- Portable line voltage iron - no base station required
- Stainless steel modular plug-in heater, greater efficiency and versatility
- Temperature is controlled by tip (600° F, 700° F, and 800° F tips)
- Nominal heat-up time with 700° F tip is 110 seconds
- Uses CT series tips found on page 43
- Heating element type: Nichrome wound, plug in
- UL and cUL listed
- Fume extraction adapter kit available- Cat. No. AKFE11



W60P



W100PG

Catalog Number

W60P
W60P3
W100PG
W100P3

Description

60 watts, 120 V, 700° F 2-wire soldering iron with CT5A7 tip
60 watts, 120 V, 700° F 3-wire soldering iron with CT5A7 tip
100 watts, 120 V, 700° F heavy duty 2-wire soldering iron with CT6F7 tip
100 watts, 120 V, 700° F heavy duty 3-wire soldering iron with CT6F7 tip



TCP12P

CONTROLLED-OUTPUT FIELD SOLDERING IRON

- Versatile controlled tool for field servicing
- Operates from 12 volt batteries or low voltage power source
- Complete with battery clips and 12' fused cord
- Soldering iron comes with PTA7 tip, creates 700° F temperature
- UL and cUL listed

