

Optional Tips

Unit : mm

SHAPE B	T15-B Shape-B	T15-B2 Shape-0.5B	T15-B3 Shape-0.7B	T15-B4 Shape-0.4B	T15-BLL Long Shape-BL
SHAPE BC	T15-BC1 Shape-1BC T15-BCF1*	T15-BC2 Shape-2BC T15-BCF2*	T15-BC3 Shape-3BC T15-BCF3*	T15-BC12 Shape-1.2BC	T15-BC15 Shape-1.5BC
SHAPE C	T15-C1 Shape-1C	T15-CF2* Shape-2C	T15-CF3* Shape-3C	T15-C4 Shape-4C T15-CF4*	
SHAPE D	T15-D08 Shape-0.8D	T15-D12 Shape-1.2D	T15-D16 Shape-1.6D	T15-D2 Shape-2D	T15-D24 Shape-2.4D
SHAPE I	T15-D32 Shape-3.2D	T15-D4 Shape-4D	T15-D52 Shape-5.2D	T15-DL4 Long Shape-4D	T15-DL52 Long Shape-5.2D
SHAPE J	T15-XD15 Shape-1.5XD				
SHAPE I	T15-I Shape-I	T15-IL Shape-IL	T15-ILS Shape-ILS		
SHAPE J	T15-JO2 Shape-0.2J	T15-JD14 Shape-1.4JD	T15-JD16 Shape-0.6JD	T15-JL02 Shape-0.2JL	T15-JS02 Shape-0.2JS

SHAPE K	T15-K Shape-K	T15-KF Shape-KF	T15-KL Shape-KL	T15-KU Shape-KU	
SHAPE R	T15-R20 Shape-2.0R	T15-R23 Shape-2.3R	T15-R27 Shape-2.7R	T15-R34 Shape-3.4R	T15-R48 Shape-4.8R
SHAPE SB	T15-SB02 Shape-0.2SB	T15-SB03 Shape-0.3SB	T15-SB05 Shape-0.5SB	T15-SB08 Shape-0.8SB	T15-SBC04 Shape-0.4SBC
TUNNEL	T15-SBS04 Shape-0.4BS	T15-SBS07 Shape-0.7BS			
QUAD	T15-1001** Tunnel 5.1 x 4.6	T15-1002** Tunnel 5.1 x 10.4	T15-1003** Tunnel 9.5 x 18.3	T15-1004** Tunnel 9.5 x 15.8	T15-1005** Tunnel 9.5 x 13.2
SPATULA	T15-1006** Tunnel 6.9 x 11.4	T15-1007** Tunnel 7.9 x 18.8	T15-1008** Tunnel 19.5 x 10.2	T15-1009** Tunnel 13.4 x 20.5	T15-1010** Tunnel 19.5 x 12
SPECIAL APPLICATIONS TYPE	T15-1201** Quad 13.6 x 8.5	T15-1202** Quad 10.3 x 10.3	T15-1203** Quad 12.8 x 12.8	T15-1204** Quad 17.9 x 17.9	T15-1205** Quad 23.4 x 17.3
SPECIAL APPLICATIONS TYPE	T15-1206** Quad 22.5 x 16.5	T15-1207** Quad 15.5 x 15.5	T15-1208** Quad 15.8 x 15.8	T15-1209** Quad 8.4 x 8.4	T15-1210** Quad 15.4 x 12.8
SPECIAL APPLICATIONS TYPE	T15-1401** Spatula 10.4	T15-1402** Spatula 15.7	T15-1403** Spatula 21.2	T15-1406** Spatula 40	
SPECIAL APPLICATIONS TYPE	T15-BCM2*** Shape-2BC Bevel with indent	T15-BCM3*** Shape-3BC Bevel with indent	T15-1603** Shape-Long reach chisel	T15-1605** Shape-Long reach chisel	

* These tips are tinned on the soldering surface only.
 ** The iron tips marked with double asterisk (**) have a temperature accuracy of ±25°C. Others have a temperature accuracy of ±15°C.
 *** T15-BCM2 and T15-BCM3 are not available for sale or use in the U.S.A.