

DIGITAL MULTIMETER

MY60/MY61/MY62

MY60

VOLTAGE AC 750V
DC 1000V

CURRENT AC 10A
DC 10A



hFE β \rightarrow \rightarrow

Auto Power Off (Apo) \rightarrow



MY61

VOLTAGE AC 750V
DC 1000V

CURRENT AC 10A
DC 10A



hFE β \rightarrow \rightarrow

Auto Power Off (Apo) \rightarrow



MY62

VOLTAGE AC 750V
DC 1000V

CURRENT AC 10A
DC 10A



hFE β \rightarrow \rightarrow $^{\circ}\text{C}$

Auto Power Off (Apo) \rightarrow



Features:

- ▶ Rugged Shell Design
- ▶ Large Digital LCD Display
- ▶ Tests AC/DC Voltage and Current, Resistance, Capacitance and Frequency
- ▶ Transistor Check, Diode and Continuity Test
- ▶ Type-K thermocouple contact temperature measurement [MY62]
- ▶ Data Hold and Auto Power Off

EMC
LVD



Specifications

		MY60	MY61	MY62
Specifications	Range	Accuracy		
DC Voltage	200mV/2V/20V/200V	$\pm(0.5\%+3)$	$\pm(0.5\%+3)$	$\pm(0.5\%+3)$
	1000V	$\pm(0.8\%+3)$	$\pm(0.8\%+3)$	$\pm(0.8\%+3)$
AC Voltage	200mV	$\pm(1.2\%+3)$	$\pm(0.8\%+3)$	$\pm(0.8\%+3)$
	2V/20V/200V	$\pm(0.8\%+3)$	$\pm(0.8\%+3)$	$\pm(0.8\%+3)$
DC Current	750V	$\pm(1.2\%+3)$	$\pm(1.2\%+3)$	$\pm(1.2\%+3)$
	20 μ A	$\pm(2.0\%+5)$		
	200 μ A	$\pm(0.8\%+3)$		
AC Current	2mA/20mA/200mA	$\pm(1.5\%+1)$	$\pm(1.5\%+1)$	$\pm(1.5\%+1)$
	10A	$\pm(2.0\%+5)$	$\pm(2.0\%+5)$	$\pm(2.0\%+5)$
	20 μ A/200 μ A	$\pm(1.8\%+5)$		
Resistance	2mA/20mA/200mA	$\pm(1.8\%+5)$	$\pm(1.8\%+5)$	$\pm(1.8\%+5)$
	10A	$\pm(3.0\%+5)$	$\pm(3.0\%+5)$	$\pm(3.0\%+5)$
	200 Ω /2K Ω /20K Ω /200K Ω /2M Ω	$\pm(0.8\%+3)$	$\pm(0.8\%+3)$	$\pm(0.8\%+3)$
Capacitance	20M Ω	$\pm(1.0\%+5)$	$\pm(1.0\%+5)$	$\pm(1.0\%+5)$
	200 M Ω	$\pm(6.0\%+10)$	$\pm(6.0\%+10)$	$\pm(6.0\%+10)$
Temperature($^{\circ}\text{C}$)	2nf/20nf/200nf/2 μ F		$\pm(4.0\%+3)$	$\pm(4.0\%+3)$
	100 μ F		$\pm(6.0\%+10)$	$\pm(6.0\%+10)$
Features				
Display	counts	2000	2000	2000
Transistor hFE	0~1000	●	●	●
Diode	2.7V	●	●	●
Continuity Buzzer	<50 Ω	●	●	●
Data Hold		●	●	●
Apo	Auto Power Off	●	●	●
LBD	Low Battery Display	●	●	●
General				
Power Supply	1x9V 6F22 Battery			
Product Size	195mmx95mmx55mm/7.67"x3.74"x2.16"			
Product Weight	366g/0.8lb			
Safety Rating	CE ETL CAT.II 1000V CAT.III 600V RoHS			